

NEW Aquarea High Performance Hydraulic Split All in One L Generation Single phase. Heating and Cooling - R290

Natural refrigerant R290 with GWP 3.

Energy efficiency: A+++ in heating at 35 °C and A+ in DHW / DHW up to 65 °C without heater / Stainless steel DHW tank with U-Vacua™ insulation panel / DHW COP up to 3,60.

Flexibility: Hydraulic connection between indoor and outdoor / Built-in magnetic water filter.

Comfort: Operation without backup heating at -25 °C / 75 °C water outlet temperature maximum at -10 °C outside temperature / 55 °C hot water even at -25 °C outside temperature.

Control: Optimised user interface and improved features (2 zone control, bivalent control).

Connectivity: Wi-Fi adapter included.



Single phase (power to indoor)			
Kit 3 kW electric heater		KIT-ADC05L3E5	KIT-ADC07L3E5
Kit 6 kW electric heater		KIT-ADC05L6E5	KIT-ADC09L6E5
Heating capacity / COP (A +7 °C, W 35 °C)	kW / COP	5,00 / 5,05	7,00 / 4,93
Heating capacity / COP (A +7 °C, W 55 °C)	kW / COP	5,00 / 3,07	7,00 / 2,98
Heating capacity / COP (A +2 °C, W 35 °C)	kW / COP	5,00 / 3,52	6,85 / 3,43
Heating capacity / COP (A +2 °C, W 55 °C)	kW / COP	5,00 / 2,34	6,25 / 2,34
Heating capacity / COP (A -7 °C, W 35 °C)	kW / COP	5,00 / 3,01	5,80 / 3,01
Heating capacity / COP (A -7 °C, W 55 °C)	kW / COP	5,00 / 2,12	5,80 / 2,12
Cooling capacity / EER (A 35 °C, W 7 °C)	kW / EER	5,00 / 3,23	7,00 / 3,03
Cooling capacity / EER (A 35 °C, W 18 °C)	kW / EER	5,00 / 5,00	7,00 / 4,73
Heating average climate (W 35 °C / W 55 °C)	Seasonal energy efficiency SCOP (η _s %)	5,06 / 3,63 [200 / 142]	4,96 / 3,62 [195 / 142]
	Energy class ¹⁾	A+++ to D	A+++ / A++
Heating warm climate (W 35 °C / W 55 °C)	Seasonal energy efficiency SCOP (η _s %)	6,00 / 4,27 [237 / 168]	6,31 / 4,52 [249 / 178]
	Energy class ¹⁾	A+++ to D	A+++ / A+++
Heating cold climate (W 35 °C / W 55 °C)	Seasonal energy efficiency SCOP (η _s %)	4,25 / 3,28 [167 / 128]	4,25 / 3,29 [167 / 129]
	Energy class ¹⁾	A+++ to D	A++ / A++
Indoor unit 3 kW electric heater		WH-ADC0509L3E5	WH-ADC0509L3E5
Indoor unit 6 kW electric heater		WH-ADC0509L6E5	WH-ADC0509L6E5
Sound pressure	Heat / Cool	dB(A)	28 / 28
Dimension	H x W x D	mm	1642 x 599 x 602
Net weight 3 kW / 6 kW		kg	93 / 94
Water pipe connector	Room	Inch	1 1/4
	Shower	Inch	3/4
A class pump	Number of speeds	Variable Speed	Variable Speed
	Input power (Min/Max)	W	30 / 145
Heating water flow (ΔT=5 K, 35 °C)		L/min	14,3
Water volume		L	185
Maximum DHW temperature		°C	65
Material inside tank		Stainless steel	Stainless steel
Tapping profile according EN16147		L	L
DHW tank ERP efficiency average / warm / cold ²⁾	A+ to F	A+ / A+ / A	A+ / A+ / A
DHW tank ERP average climate η / COPdHW	η _{wh} % / COPdHW	146 / 3,60	146 / 3,60
DHW tank ERP warm climate η / COPdHW	η _{wh} % / COPdHW	160 / 4,00	160 / 4,00
DHW tank ERP cold climate η / COPdHW	η _{wh} % / COPdHW	112 / 2,80	112 / 2,80
Outdoor unit		WH-WDG05LE5	WH-WDG07LE5
Sound power ³⁾	Heat	dB(A)	52
Dimension / Net weight	H x W x D	mm / kg	996 x 980 x 430 / 98
Refrigerant (R290) / CO ₂ Eq.		kg / T	0,96 / 0,003
Water pipe connector (indoor / outdoor units)		Inch	1 / 1
Pipe length range standard / maximum		m	5 / 30
Elevation difference (in / out)		m	10
Operating range - outdoor ambient	Heat	°C	-25 ~ +35
	Cool	°C	+10 ~ +43
Water outlet	Heat / Cool	°C	20 ~ 75 / 5 ~ 20

Electrical information	3 kW heater	6 kW heater	3 kW heater	6 kW heater	3 kW heater	6 kW heater
Electric backup heater	kW	3,00	6,00	3,00	6,00	6,00
Recommended RCD, supply 1 / 2	A	25 / 16	25 / 30	25 / 16	25 / 30	25 / 30
Recommended minimum cable size, supply 1 / 2 ⁴⁾	mm ²	3x2,5/3x1,5	3x2,5/3x4,0	3x2,5/3x1,5	3x2,5/3x4,0	3x2,5/3x4,0

1) Scale from A+++ to D, 2) Scale from A+ to F, 3) The sound power level is measured with accordance to EN12102 under conditions of the EN14825 (part load), 4) Check local regulations, * EER and COP calculation is based in accordance to EN14511, ** This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

Accessories	
CZ-RTW1	Additional remote controller for K and L Generations
CZ-NS5P	Additional functions PCB
PAW-A2W-RTWIRED	Room thermostat

Accessories	
PAW-A2W-RTWIREDLESS	Wireless LCD room thermostat
PAW-A2W-AFVLV	1 anti-freeze valve. It is required to order 2 valves per system



INTERNET CONTROL: Wi-Fi adapter included.

NEW Aquarea High Performance Hydraulic Split All in One L Generation Single phase. Heating and Cooling 2 zones · R290

Natural refrigerant R290 with GWP 3.

Energy efficiency: A+++ in heating at 35 °C and A+ in DHW / DHW up to 65 °C without heater / Stainless steel DHW tank with U-Vacua™ insulation panel / DHW COP up to 3,60.

Flexibility: Hydraulic connection between indoor and outdoor / Built-in magnetic water filter / 2 zone control.

Comfort: Operation without backup heating at -25 °C / 75 °C water outlet temperature maximum at -10 °C outside temperature / 55 °C hot water even at -25 °C outside temperature.

Control: Optimised user interface and improved features (2 zone control, bivalent control).

Connectivity: Wi-Fi adapter included.



Single phase (power to indoor)					
Kit			KIT-ADC05L3E5B	KIT-ADC07L3E5B	KIT-ADC09L3E5B
Heating capacity / COP [A +7 °C, W 35 °C]		kW / COP	5,00/5,05	7,00/4,93	9,00/4,55
Heating capacity / COP [A +7 °C, W 55 °C]		kW / COP	5,00/3,07	7,00/2,98	8,90/3,03
Heating capacity / COP [A +2 °C, W 35 °C]		kW / COP	5,00/3,52	6,85/3,43	7,00/3,41
Heating capacity / COP [A +2 °C, W 55 °C]		kW / COP	5,00/2,34	6,25/2,34	7,00/2,41
Heating capacity / COP [A -7 °C, W 35 °C]		kW / COP	5,00/3,01	5,80/3,01	7,00/2,80
Heating capacity / COP [A -7 °C, W 55 °C]		kW / COP	5,00/2,12	5,80/2,12	7,00/2,13
Cooling capacity / EER [A 35 °C, W 7 °C]		kW / EER	5,00/3,23	7,00/3,03	8,20/2,82
Cooling capacity / EER [A 35 °C, W 18 °C]		kW / EER	5,00/5,00	7,00/4,73	9,00/4,19
Heating average climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP [η _s %]	5,06/3,63[200/142]	4,96/3,62[195/142]	4,84/3,67[190/144]
	Energy class ¹⁾	A+++ to D	A+++/A++	A+++/A++	A+++/A++
Heating warm climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP [η _s %]	6,00/4,27[237/168]	6,31/4,52[249/178]	6,44/4,50[255/177]
	Energy class ¹⁾	A+++ to D	A+++/A+++	A+++/A+++	A+++/A+++
Heating cold climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP [η _s %]	4,25/3,28[167/128]	4,25/3,29[167/129]	4,31/3,33[170/130]
	Energy class ¹⁾	A+++ to D	A++/A++	A++/A++	A++/A++
Indoor unit			WH-ADC0509L3E5B	WH-ADC0509L3E5B	WH-ADC0509L3E5B
Sound pressure	Heat / Cool	dB(A)	28/28	28/28	28/28
Dimension	H x W x D	mm	1642 x 599 x 602	1642 x 599 x 602	1642 x 599 x 602
Net weight		kg	101	101	101
Water pipe connector	Room	Inch	1¼	1¼	1¼
	Shower	Inch	¾	¾	¾
A class pump	Number of speeds		Variable Speed	Variable Speed	Variable Speed
	Input power (Min/Max)	W	30/145	30/145	30/145
Heating water flow (ΔT=5 K, 35 °C)		L/min	14,3	20,1	25,8
Water volume		L	185	185	185
Maximum DHW temperature		°C	65	65	65
Material inside tank			Stainless steel	Stainless steel	Stainless steel
Tapping profile according EN16147			L	L	L
DHW tank ERP efficiency average / warm / cold ²⁾		A+ to F	A+/A+/A	A+/A+/A	A+/A+/A
DHW tank ERP average climate η / COP _{DHW}		η _{wh} %/COP _{DHW}	146/3,60	146/3,60	146/3,60
DHW tank ERP warm climate η / COP _{DHW}		η _{wh} %/COP _{DHW}	160/4,00	160/4,00	160/4,00
DHW tank ERP cold climate η / COP _{DHW}		η _{wh} %/COP _{DHW}	112/2,80	112/2,80	112/2,80
Outdoor unit			WH-WDG05LE5	WH-WDG07LE5	WH-WDG09LE5
Sound power ³⁾	Heat	dB(A)	52	53	54
Dimension / Net weight	H x W x D	mm / kg	996 x 980 x 430/98	996 x 980 x 430/98	996 x 980 x 430/97
Refrigerant (R290) / CO ₂ Eq.		kg / T	0,96/0,003	0,96/0,003	1,00/0,003
Water pipe connector (indoor / outdoor units)		Inch	1/1	1/1	1/1
Pipe length range standard / maximum		m	5/30	5/30	5/30
Elevation difference (in / out)		m	10	10	10
Operating range - outdoor ambient	Heat	°C	-25 ~ +35	-25 ~ +35	-25 ~ +35
	Cool	°C	+10 ~ +43	+10 ~ +43	+10 ~ +43
Water outlet	Heat / Cool	°C	20 ~ 75/5 ~ 20	20 ~ 75/5 ~ 20	20 ~ 75/5 ~ 20
Electrical information			WH-ADC0509L3E5B	WH-ADC0509L3E5B	WH-ADC0509L3E5B
Electric backup heater		kW	3,00	3,00	3,00
Recommended RCD, supply 1 / 2		A	25/16	25/16	25/16
Recommended minimum cable size, supply 1 / 2 ⁴⁾		mm²	3x2,5/3x1,5	3x2,5/3x1,5	3x2,5/3x1,5

1) Scale from A+++ to D, 2) Scale from A+ to F, 3) The sound power level is measured with accordance to EN12102 under conditions of the EN14825 (part load), 4) Check local regulations, * EER and COP calculation is based in accordance to EN14511, ** This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU, The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

Accessories	
CZ-RTW1	Additional remote controller for K and L Generations
CZ-NS5P	Additional functions PCB
PAW-A2W-RTWIRED	Room thermostat

Accessories	
PAW-A2W-RTWIREDLESS	Wireless LCD room thermostat
PAW-A2W-AFVLV	1 anti-freeze valve. It is required to order 2 valves per system



INTERNET CONTROL: Wi-Fi adapter included.

NEW Aquarea High Performance Hydraulic Split All in One L Generation Single phase. Heating and Cooling with Electrical Anode - R290

Natural refrigerant R290 with GWP 3.

Energy efficiency: A+++ in heating at 35 °C and A+ in DHW / DHW up to 65 °C without heater / Stainless steel DHW tank with U-Vacua™ insulation panel / DHW COP up to 3,60.

Flexibility: Hydraulic connection between indoor and outdoor / Built-in magnetic water filter / Installation in harsh water conditions.

Comfort: Operation without backup heating at -25 °C / 75 °C water outlet temperature maximum at -10 °C outside temperature / 55 °C hot water even at -25 °C outside temperature.

Control: Optimised user interface and improved features (2 zone control, bivalent control).

Connectivity: Wi-Fi adapter included.



Single phase (power to indoor)			
Kit 3 kW electric heater		KIT-ADC05L3E5AN	KIT-ADC07L3E5AN
Kit 6 kW electric heater		KIT-ADC05L6E5AN	KIT-ADC07L6E5AN
Heating capacity / COP [A +7 °C, W 35 °C]	kW / COP	5,00/5,05	7,00/4,93
Heating capacity / COP [A +7 °C, W 55 °C]	kW / COP	5,00/3,07	7,00/2,98
Heating capacity / COP [A +2 °C, W 35 °C]	kW / COP	5,00/3,52	6,85/3,43
Heating capacity / COP [A +2 °C, W 55 °C]	kW / COP	5,00/2,34	6,25/2,34
Heating capacity / COP [A -7 °C, W 35 °C]	kW / COP	5,00/3,01	5,80/3,01
Heating capacity / COP [A -7 °C, W 55 °C]	kW / COP	5,00/2,12	5,80/2,12
Cooling capacity / EER [A 35 °C, W 7 °C]	kW / EER	5,00/3,23	7,00/3,03
Cooling capacity / EER [A 35 °C, W 18 °C]	kW / EER	5,00/5,00	7,00/4,73
Heating average climate [W 35 °C / W 55 °C]	Seasonal energy efficiency SCOP (η _s %)	5,06/3,63[200/142]	4,96/3,62[195/142]
	Energy class ¹⁾	A+++ to D	A+++ / A++
Heating warm climate [W 35 °C / W 55 °C]	Seasonal energy efficiency SCOP (η _s %)	6,00/4,27[237/168]	6,31/4,52[249/178]
	Energy class ¹⁾	A+++ to D	A+++ / A+++
Heating cold climate [W 35 °C / W 55 °C]	Seasonal energy efficiency SCOP (η _s %)	4,25/3,28[167/128]	4,25/3,29[167/129]
	Energy class ¹⁾	A+++ to D	A++ / A++
Indoor unit 3 kW electric heater		WH-ADC0509L3E5AN	WH-ADC0509L3E5AN
Indoor unit 6 kW electric heater		WH-ADC0509L6E5AN	WH-ADC0509L6E5AN
Sound pressure	Heat / Cool	dB(A)	28/28
Dimension	H x W x D	mm	1642 x 599 x 602
Net weight 3 kW / 6 kW		kg	93/94
Water pipe connector	Room	Inch	1 1/4
	Shower	Inch	3/4
A class pump	Number of speeds	Variable Speed	Variable Speed
	Input power (Min/Max)	W	30/145
Heating water flow (ΔT=5 K, 35 °C)		L/min	14,3
Water volume		L	185
Maximum DHW temperature		°C	65
Material inside tank		Stainless steel	Stainless steel
Tapping profile according EN16147		L	L
DHW tank ERP efficiency average / warm / cold ²⁾	A+ to F	A+ / A+ / A	A+ / A+ / A
DHW tank ERP average climate η / COPdHW	η _{wh} % / COPdHW	146/3,60	146/3,60
DHW tank ERP warm climate η / COPdHW	η _{wh} % / COPdHW	160/4,00	160/4,00
DHW tank ERP cold climate η / COPdHW	η _{wh} % / COPdHW	112/2,80	112/2,80
Outdoor unit		WH-WDG05LE5	WH-WDG07LE5
Sound power ³⁾	Heat	dB(A)	52
Dimension / Net weight	H x W x D	mm / kg	996 x 980 x 430/98
Refrigerant (R290) / CO ₂ Eq.		kg / T	0,96/0,003
Water pipe connector (indoor / outdoor units)		Inch	1/1
Pipe length range standard / maximum		m	5/30
Elevation difference (in / out)		m	10
Operating range - outdoor ambient	Heat	°C	-25 ~ +35
	Cool	°C	+10 ~ +43
Water outlet	Heat / Cool	°C	20 ~ 75/5 ~ 20
Electrical information		3 kW heater	6 kW heater
Electric backup heater	kW	3,00	6,00
Recommended RCD, supply 1 / 2	A	25/16	25/30
Recommended minimum cable size, supply 1 / 2 ⁴⁾	mm ²	3x2,5/3x1,5	3x2,5/3x4,0
		3 kW heater	6 kW heater
Electric backup heater	kW	3,00	6,00
Recommended RCD, supply 1 / 2	A	25/16	25/30
Recommended minimum cable size, supply 1 / 2 ⁴⁾	mm ²	3x2,5/3x1,5	3x2,5/3x4,0

1) Scale from A+++ to D, 2) Scale from A+ to F, 3) The sound power level is measured with accordance to EN12102 under conditions of the EN14825 (part load), 4) Check local regulations, * EER and COP calculation is based in accordance to EN14511, ** This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

Accessories	
CZ-RTW1	Additional remote controller for K and L Generations
CZ-NS5P	Additional functions PCB
PAW-A2W-RTWIRED	Room thermostat

Accessories	
PAW-A2W-RTWIRED	Wireless LCD room thermostat
PAW-A2W-AFVLV	1 anti-freeze valve. It is required to order 2 valves per system



INTERNET CONTROL: Wi-Fi adapter included.

NEW Aquarea High Performance Hydraulic Split Bi-bloc L Generation Single phase. Heating and Cooling - R290

Natural refrigerant R290 with GWP 3.

Energy efficiency: A+++ in heating at 35 °C / Built-in flow meter.

Flexibility: Hydraulic connection between indoor and outdoor / Built-in magnetic water filter / Installation possible in sites with harsh water quality.

Comfort: Operation without backup heating at -25 °C / 75 °C water outlet temperature maximum at -10 °C outside temperature / 55 °C hot water even at -25 °C outside temperature.

Control: Optimised user interface and improved features [2 zone control, bivalent control].

Connectivity: Wi-Fi adapter included.



Tentative data

			Single phase (power to indoor)			
Kit 3 kW electric heater			KIT-WC05L3E5	KIT-WC07L3E5	KIT-WC09L3E5	
Kit 6 kW electric heater			KIT-WC05L6E5	KIT-WC07L6E5	KIT-WC09L6E5	
Heating capacity / COP [A +7 °C, W 35 °C]	kW / COP		5,00 / 5,05	7,00 / 4,93	9,00 / 4,55	
Heating capacity / COP [A +7 °C, W 55 °C]	kW / COP		5,00 / 3,07	7,00 / 2,98	8,90 / 3,03	
Heating capacity / COP [A +2 °C, W 35 °C]	kW / COP		5,00 / 3,52	6,85 / 3,43	7,00 / 3,41	
Heating capacity / COP [A +2 °C, W 55 °C]	kW / COP		5,00 / 2,34	6,25 / 2,34	7,00 / 2,41	
Heating capacity / COP [A -7 °C, W 35 °C]	kW / COP		5,00 / 3,01	5,80 / 3,01	7,00 / 2,80	
Heating capacity / COP [A -7 °C, W 55 °C]	kW / COP		5,00 / 2,12	5,80 / 2,12	7,00 / 2,13	
Cooling capacity / EER [A 35 °C, W 7 °C]	kW / EER		5,00 / 3,23	7,00 / 3,03	8,20 / 2,82	
Cooling capacity / EER [A 35 °C, W 18 °C]	kW / EER		5,00 / 5,00	7,00 / 4,73	9,00 / 4,19	
Heating average climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η _s %)	5,06 / 3,63 [200 / 142]	4,96 / 3,62 [195 / 142]	4,84 / 3,67 [190 / 144]	
	Energy class ¹⁾		A+++ / A++	A+++ / A++	A+++ / A++	
Heating warm climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η _s %)	6,00 / 4,27 [237 / 168]	6,31 / 4,52 [249 / 178]	6,44 / 4,50 [255 / 177]	
	Energy class ¹⁾		A+++ / A+++	A+++ / A+++	A+++ / A+++	
Heating cold climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η _s %)	4,25 / 3,28 [167 / 128]	4,25 / 3,29 [167 / 129]	4,31 / 3,33 [170 / 130]	
	Energy class ¹⁾		A++ / A++	A++ / A++	A++ / A++	
Indoor unit 3 kW electric heater			WH-SDC0509L3E5	WH-SDC0509L3E5	WH-SDC0509L3E5	
Indoor unit 6 kW electric heater			WH-SDC0509L6E5	WH-SDC0509L6E5	WH-SDC0509L6E5	
Sound pressure	Heat / Cool	dB(A)	28 / 28	30 / 30	30 / 31	
Dimension	H x W x D	mm	892 x 500 x 348	892 x 500 x 348	892 x 500 x 348	
Net weight		kg	—	—	—	
Water pipe connector	Room	Inch	R 1¼	R 1¼	R 1¼	
A class pump	Number of speeds		Variable Speed	Variable Speed	Variable Speed	
	Input power [Min / Max]	W	30 / 145	30 / 145	30 / 145	
Heating water flow [ΔT=5 K, 35 °C]		L/min	—	—	—	
Outdoor unit			WH-WDG05LE5	WH-WDG07LE5	WH-WDG09LE5	
Sound power ²⁾	Heat	dB(A)	52	53	54	
Dimension	H x W x D	mm	996 x 980 x 430	996 x 980 x 430	996 x 980 x 430	
Net weight		kg	98	98	97	
Refrigerant (R290) / CO ₂ Eq.		kg / T	0,96 / 0,003	0,96 / 0,003	1,00 / 0,003	
Water pipe connector (indoor / outdoor units)		Inch	1 / 1	1 / 1	1 / 1	
Pipe length range standard / maximum		m	5 / 30	5 / 30	5 / 30	
Elevation difference (in / out)		m	10	10	10	
Operating range - outdoor ambient	Heat	°C	-25 ~ +35	-25 ~ +35	-25 ~ +35	
	Cool	°C	+10 ~ +43	+10 ~ +43	+10 ~ +43	
Water outlet	Heat / Cool	°C	20 ~ 75 / 5 ~ 20	20 ~ 75 / 5 ~ 20	20 ~ 75 / 5 ~ 20	
Electrical information			3 kW heater	6 kW heater	3 kW heater	6 kW heater
Electric backup heater	kW		3,00	6,00	3,00	6,00
Recommended fuse	A		25 / 16	25 / 30	25 / 16	25 / 30
Recommended minimum cable size, supply 1 / 2 ³⁾	mm ²		3x2,5/3x1,5	3x2,5/3x4,0	3x2,5/3x1,5	3x2,5/3x4,0

1) Scale from A+++ to D. 2) The sound power level is measured with accordance to EN12102 under conditions of the EN14825 (part load). 3) Check local regulations. * EER and COP calculation is based in accordance to EN14511. ** This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility. *** Tentative data.

Accessories	
CZ-RTW1	Additional remote controller for K and L Generations
PAW-TD20C1E5-1	Tank 200 L - Stainless steel
PAW-TD30C1E5-1	Tank 300 L - Stainless steel
PAW-TA20C1E5STD	Tank 200 L - Enamelled
PAW-TA30C1E5STD	Tank 300 L - Enamelled
PAW-3WYVLV-HW	3 way valve for DHW tanks
CZ-NV2	3 way valve kit for inside of hydrokit for K and L Generations

Accessories	
PAW-BTANK50L-2	Buffer tank 50 L
CZ-NS5P	Additional functions PCB
PAW-A2W-RTWIRED	Room thermostat
PAW-A2W-RTWIREDLESS	Wireless LCD room thermostat
PAW-A2W-AFVLV	1 anti-freeze valve. It is required to order 2 valves per system



INTERNET CONTROL: Wi-Fi adapter included.